



METAL GATE STATION

Your Stylish Entryway Guardian





METAL GATE STATION

This isn't just any gate station - it's a statement piece built to impress. Crafted from sleek aluminium that's as robust as it is sophisticated, it endures the elements while adding a touch of modern elegance to your property. Forget plastic enclosures - this gate station makes a lasting first impression.

But beauty is more than skin deep. With the **G-SPEAK ULTRA**, convenience and security go hand-in-hand. Answer calls from anywhere using your cellular device, granting access or checking in with visitors remotely. No more being tied to a physical handset. For added peace of mind, the station boasts backlit buttons for clear visibility even at night, ensuring easy operation in any lighting condition.

And for ultimate customisation, the gate station effortlessly integrates with the universal gooseneck (sold separately), providing the perfect finishing touch to your unique entryway style.

Experience the next level of intercom convenience and security, all wrapped in a design that turns heads. Choose the **Metal Gate Station** today.

FEATURES AND BENEFITS

- Answer your intercom from anywhere, using your cellular device - enhanced security and convenience
- No messy and expensive wiring
- 1, 2 or 4 call buttons with the ability to add two numbers per button and Time Barring configurable per button (for example; automatically disable primary button at night)
- Backlit button(s)
- Rugged aluminium enclosure
- The mounting holes are compatible with our Universal Gooseneck¹

1. Requires a Gooseneck backing plate to maintain IP rating.

TECHNICAL SPECIFICATIONS

Technical Data	METAL GATE STATION ¹
Operating voltage ²	7.4V DC as supplied by the G-SPEAK ULTRA ³
Current draw	11mA
Speech volume	Adjustable via G-WEB
Wiring	6 wire connection (power, audio and mic)
Ring tone	Electronic when button is depressed
Call confirmation	Yes
Call buttons	1, 2 or 4 (illuminated with labels)
Operating temperature	-20°C to +50°C
Humidity	0 - 90% non-condensing
Degree of protection	IP54 ⁴
Dimensions	97mm wide x 40mm deep x 178mm high

1. Requires a **G-SPEAK ULTRA** device, as the Gate Station cannot be used on its own.
2. If the 12V DC gate motor supply dips when the motor starts up and the intercom is being used at the same time, the speech quality might be affected.
3. The Gate Station must only be powered via a **G-SPEAK ULTRA** Device.
4. A Gooseneck backing plate is required when mounting onto a Gooseneck, to maintain IP rating.

OVERALL DIMENSIONS

